



3RXXA-TP1

3RXXA-TP

项目 Item	规格 Specification							单位 Unit
	3R75A-TP1	3R90A-TP1	3R230A-TP1	3R300A-TP1	3R350A-TP1	3R420A-TP1	3R470A-TP1	
	3R75A-TP	3R90A-TP	3R230A-TP	3R300A-TP	3R350A-TP	3R420A-TP	3R470A-TP	
标称直流击穿电压 Nominal DC Spark-over Voltage (100V/S)	75 ± 25%	90 ± 20%	230 ± 20%	300 ± 20%	350 ± 20%	420 ± 20%	470 ± 20%	V
最大冲击击穿电压 Maximum impulse spark- over voltage (1KV/us)	600	600	650	800	900	950	1000	V
耐冲击电流 (短波) Impulse discharge current (8/20us, 10 times) (a+b)-e	5	5	5	5	5	5	5	KA
耐交流电流 AC discharge current (50HZ, IS, 10 times)	5	5	5	5	5	5	5	A
最小绝缘电阻 Minimum insulation resistance	1000	1000	1000	1000	1000	1000	1000	MΩ
最大极间电容 Maximum capacitance (1MHZ)	1.2	1.2	1.2	1.2	1.2	1.2	1.2	pF